

36" 44"

THE INDUSTRY-LEADING SCANNER FOR LARGE FORMAT TECHNICAL DRAWINGS

NEW!

SCAN FASTER AND SMARTER WITH MORE PRECISION IN EVERY PIXEL

The all new and perfected IQ Quattro X is a must have for every high-production environment.

Faster: IQ Quattro X is the 5th generation of Contex CIS scanners, with enhanced speed and 3 times faster data transfer, the scanner is the essence of productivity.

Smarter: The Nextimage Remote app offers you a completely new way of working. The new app saves valuable operator time by bringing all main functions essential for basic scanning and copying in front of the operator directly on the scanner.

Better: Contex Live Alignment is a new IQ Quattro X technology designed to improve image alignment across sensors ensuring precise and sharp alignment all the time, no matter the speed.

Improved technology: Contex USB 3.0 implementation with xDTR3 is blisteringly fast and you won't have to worry about shoe shining or rescanning to get the width right.

Image quality

The 48-bit CIS technology captures every detail from your document, then passes the best 24-bits through to the file at up to 1200 dpi optical resolution.

Fastest CIS scanner

The IQ Quattro X scanners produce a scan speed of up to 17.8 inches per second in RGB color and 200 dpi.

3-position speed control

Great for use with delicate originals. Temporarily shift down to slower scan speeds without using presets or altering software.

Green technology

Energy Star® version 3.0 compliant using only 0.5W in standby mode.

High productivity

Enhanced speed and data transfer rates makes the IQ Quattro X the essence of productivity.

OUTSTANDING IMAGE QUALITY AND PRODUCTIVITY

SEE MORE: contex.com/igguattrox






	IQ QUATTRO X 3650	IQ QUATTRO X 3690	IQ QUATTRO X 4450	IQ QUATTRO X 4490	
Maximum scan width	36 inch (914 mm)		44 inch (1118 mm)		
Maximum media width	38 inch (965 mm)		47 inch (1194 mm)		
Scanning speed1 (inch/sec.) 36-inch	n wide document				
200 dpi RGB color Upgradeable	8.9 Yes, to 17.8	17.8	8.9 Yes, to 17.8	17.8	
200 dpi grayscale/monochrome	17.8				
Productivity (documents/hour) Batch scanning for 60 minutes (200 dpi). Includes paper load and eject time. Measured in completed scans					
Arch E-size, portrait, RGB color Arch E-size, portrait, monochrome	523 856	856	523 856	856	
Specifications					
Maximum media thickness	0.08 in (2 mm) flexible documents				
Optical resolution	1200 dpi				
Maximum resolution	9600 dpi (interpolated)				
Total number of pixels	54000 pixels 64800 pixels) pixels		
Contex key CIS technologies	CleanScan ² , SIGMA ³ , CFR ⁴				
Document justification	Flexible center load, due to autosize				
Accuracy	0.1% +/- 1 pixel				
Data capture color depth	48-bit color/16-bit monochrome				
Color spaces	Adobe RGB, Device RGB, RAW RGB, sRGB				
USB connection	USB 3.0 with xDTR3				
Ethernet connection	Gigabit with xDTR2.5				
Networking protocols	Push and pull				
Energy Star®	Yes, version 3.0				
Included software	Nextimage 30 day trial (incl. TWAIN driver, excl. licence)				
Optional software	Nextimage Scan+Archive, Nextimage Repro, Nextimage Remote tablet app5 (free download for iOS and Android)				
File formats ⁵	TIF, JPG, PDF, PDF/A, DWF, CALS, BMP, JPEG-2000(JP2), JPEG2000 Extended (JPX), TIF-G3, TIF-G4 and others				
Printer support ⁵	HP, Canon, Epson and Océ printers. See contex.com/nextimage-supported-printers for full list				
Operating systems	Windows Server 2019 64-bit, Windows 11 64-bit, Windows 10 64-bit + 32 bit				
Power consumption (ready/sleep/scan)	18W max. / <1W / 37W (built-in power supply)				
Power supply	100-240 V, 60/50 Hz				
Weight	48.3 lbs (21.9 kg)		54 lbs (24.5 kg)		
Dimensions	45.7×19.3×6.3 in (45.7×19.3×6.3 in (1160×489×161 mm)		53.1×19.3×6.3 in (1349×489×161 mm)	
Certifications/compliance	CE, cUL/UL, CCC, EAC, UKR, BIS, FCC Class A, ICES, EMC, VCCI, KC, EuP, WEEE, RoHS, REACH and ENERGY STAR® certified				
Country of origin	Designed and engineered in Denmark, Europe. Manufactured in China.				
Scanner stand (optional)	Low adjustable stand (3 settings): 32.6/33.8/34.8 in (827/859/884 mm) High adjustable stand (9 settings): 43 to 50.9 inches in steps of 1 inch (1092 to 1292 mm in 25 mm steps)				
ScanStation Pro compatibility			Y	es	

- 1. Test equipment: Nextimage 5 software, Intel Core i7 4770K 3.5 GHz ,16 GB RAM, 1TB SSD, SuperSpeed USB 3.0 PC, Win 64-bit Contex recommends Intel Core i5, AMD Ryzen 5 5500, or better 64-bit processors, 16 GB RAM and SSD SATA drive, min. USB 3.0 or Gigabit Ethernet
- Contex CleanScan is a Contex innovation comprising dual-sided and dual-diffused LEDs in a single custom-built CIS module
- Contex Signal Intensity Matching (SIGMA) is a Contex patent that reduces the effects of uneven heat build-up in CIS sensors during scanning Contex Color Fringe Removal (CFR) is a Contex patent that sharpens images by filtering out the fringes produced by strobing CIS devices
- 5. Nextimage scanning software required


Tablet not included.

All trademarks remain the property of their respective holders, and are used only to directly describe the product being provided. Their use does not indicate a relationship between Contex and the trademark holders.

IQ Quattro X: High data transfer - superior image quality



Contex CleanScan CIS The IQ Quattro Scanners are equipped with Contex CleanScan CIS modules which facilitate optical image quality with dual-sided LED lighting. This eliminates creases and folds in originals normally a challenge for CIS scanners, and thus provides clear, crisp scans every time.



Color fringe removal (CFR) technology Color Fringe Removal (CFR) is an

advanced Contex patented filtering technology designed to remove the fringes inherent in CIS strobing scanning devices.

Contex solutions are compatible with all leading large-format printers. See the full list at contex.com/nextimage-supported-printers













contex.com/iqquattrox

